



BV LCIE  
CHINA  
Number

N° 1666AS07SXP21405

## ATTESTATION of conformity with European Directives



*Product:* **Grid-tied photovoltaic inverter**  
*Reference* **X1-1.1-S-D, X1-1.1-S-N, X1-1.5-S-D, X1-1.5-S-N, X1-2.0-S-D, X1-2.0-S-N,  
X1-2.5-S-D, X1-2.5-S-N, X1-3.0-S-D, X1-3.0-S-N, X1-3.3-S-D, X1-3.3-S-N.**  
*Issued to* **SOLAX POWER CO., LTD**  
*Address* **No. 288 Shizhu Road, Tonglu Economic Development Zone, Dongxing  
District 311500, Tonglu City, Zhejiang Province, People's Republic of  
China**  
*Manufacturer* **SolaX Power Co., Ltd**  
*Technical characteristics* **See Next Page**

The submitted sample of the above equipment has been tested for  marking according to following European Directive and following standards:

### Low Voltage Directive 2014/35/EU

Standards	Report number	Report date
EN 62109-1: 2010	SXP-16JA0323FTSP-1	29/07/2016
EN 62109-2: 2011	SXP-16JA0323FTSP-2	29/07/2016

The referred test report(s) show that the product complies with standard(s) recognized as giving presumption of compliance with the essential requirements in the specified European Directive

This verification does not imply assessment of the production of the product  
The  marking may be affixed if all relevant and effective European Directives with  are applicable

Shanghai (P.R. China), ), July 29<sup>th</sup>, 2016.



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.  
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA  
必维欧亚电气技术咨询服务(上海)有限公司  
Version 3/2016.02.19

Building 4, No. 518, Xin Zhuan Road,  
CaoHejing Songjiang High-Tech Park,  
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000  
Fax: +86 21 6195 7001  
Email: [contact@cn.bureauveritas.com](mailto:contact@cn.bureauveritas.com)



LCIE

BV LCIE  
CHINA  
Number

N° 1666AS07SXP21405

Model / Type :	X1-1.1-S-D X1-1.1-S-N	X1-1.5-S-D X1-1.5-S-N	X1-2.0-S-D X1-2.0-S-N
MPP DC voltage range [V] :	70-380	70-380	70-380
Input DC voltage range [V] :	70-400	70-400	70-400
Input DC current [A] :	10,0	10,0	10,0
Output AC voltage [V] :	220/230/240 Vac, 50/60Hz	220/230/240 Vac, 50/60Hz	220/230/240 Vac, 50/60Hz
Max.Output AC current [A] :	5,5	7,5	9,5
Output power [VA] :	1100	1500	2000

Model / Type :	X1-2.5-S-D X1-2.5-S-N	X1-3.0-S-D X1-3.0-S-N	X1-3.3-S-D X1-3.3-S-N
MPP DC voltage range [V] :	100-580	100-580	100-580
Input DC voltage range [V] :	100-600	100-600	100-600
Input DC current [A] :	10,0(Max)	10,0(Max)	10,0(Max)
Output AC voltage [V] :	220/230/240 Vac, 50/60Hz	220/230/240 Vac, 50/60Hz	220/230/240 Vac, 50/60Hz
Max.Output AC current [A] :	12	14	15
Output power [VA] :	2500	3000	3300

Shanghai (P.R. China), July 29<sup>th</sup>, 2016.



Sam Shen  
Technical Manager



This document shall not be reproduced, except in full, without the written approval of BV LCIE China.  
Information given in this document, are related to the tested specimen of the described electrical sample.

LCIE CHINA  
必维欧亚电气技术咨询服务(上海)有限公司

Building 4, No. 518, Xin Zhuan Road,  
CaoHejing Songjiang High-Tech Park,  
Shanghai P.R.C (201612)

Tel: +86 21 6195 7000  
Fax: +86 21 6195 7001  
Email: [contact@cn.bureauveritas.com](mailto:contact@cn.bureauveritas.com)

Version 3/2016.02.19